



# Architectural Lighting

## LED Pro Wash with 3W LED's! Indoor/Outdoor Use



Click for more

The LED Pro Wash is a professional, energy savings, high power, architectural/entertainment, stage, commercial, club, wash fixture which covers all the applications where smooth, rich color wash is required.

Capable of Clean RGB Color mixing, Color Temperature Correction, and is IP-65 Rated.

**Specifications:**

**LEDs:** 24-1w Red LED, 18-3w Green LED, 7-3-w Blue LED

**Voltage:** 100-120V AC/60Hz 220-240V/50Hz

**Dimensions:** L376XW232XH432mm

**Control:** 5 program cues, each can contain 10 scenes with 36 times events set to any clock time! DMX512, stand alone, scene selection system. White balance control.

Built-in thermo sensor working under 60 degrees C.

## OUTDOOR LED EXCEL -1W RGB PAI



**Power:** AC90-250V, 50/60Hz 58W

**IP Rating:** IP66

**LED's:** 36 1WLED's (12 Red, 12 Green, 12 Blue)

**Beam Angle:** Angle: 16°

**Complies with CE and ROHS Standards**

**Control:** DMX-512 (5 Channels) Adjust, Master/Slave

**Unit Dimensions:** 10.1" x 8.2" x 6.1"

**Unit Weight:** 7.7 lb Shipping Weight 12lb

**Shipping Dimensions:** 13" x 11" x 11"



### Design 150

**LAMP OPTIONS:**

HSD 150/70 (Osram)

Color temperature: 7000°K

Socket: G12

Manufacturers Rated Lamp Life: 2000 Hours

CDM-SA/T 150/942 (Philips)

Color temperature: 4200°K

Socket: G12

Manufacturers Rated Lamp Life: 6000 Hours

COLORS: Cyan, Yellow, Magenta color mixing, with crossfade effect at various speeds.



**SHUTTER/STROBE:** Double blade shutter for blackout and linear dimming.

**BEAM ANGLE:** 21°

**HEAD ADJUSTMENT:** Tilt 90° (manually adjustable).

**CONTROL:**

DMX: 6 Channels

Automatic mode with Master/Slave operation.

Lamp and unit time indication.

**MOTORS:** 8 Stepper motors

**HOUSING:** Cast Aluminum with epoxy powder paint finish.

**IP RATING:** IP65

**DIMENSIONS:** 11 in. (L) x 15 in. (W) x 20.5 in. (H) **WEIGHT:** 38.8 lbs.

### Design 250



The Design 250 is a projector of innovative, compact, silent color changing, capable of extraordinary performances in terms of color mixing, reliability and versatility. The product complies to CE norms and standards and uses international protocol DMX 512. The Design 250 is particularly suitable for television studios and theaters, stage lighting, limelight's, backdrops, inside or outside shops and shopping centers, sport centers and almost all architectural applications. The Design 250 features 6 kinds of color filters for CYM colour mixing and 2 blades for shutter/dimmer. The product has light level sensor track system, which can adjust the status of product automatically. And the projector can be setup easily via the touch-switches and LCD display. Comes with barndoor accessory

**Specifications:**

**POWER:** 117V/60Hz

**LAMP OPTIONS:** Philips CDM-T SA/T150/942 discharge lamp

Color temperature: 4200°K

Socket: G12

Manufacturers Rated Lamp Life: 6000 Hours FLUX: 12,900lm

Color temperature: 4200°K

Socket: G12

COLORS: Cyan, Yellow, Magenta color mixing, with crossfade effect at various speeds.

**SHUTTER/STROBE:** Double blade shutter for blackout and linear dimming from 0-100%

**BEAM ANGLE:** 21°

**HEAD ADJUSTMENT:** Tilt 90° (manually adjustable).

**CONTROL:**

DMX: 7 Channels

Automatic mode with Master/Slave operation.

Lamp and unit time indication.

2 user memories and 3 preset memories

**OTHER FUNCTIONS:**

Light level sensor

Timer mode

Remote reset

Lamp Control

**MOTORS:** 8 Stepper motors

**HOUSING:** Cast Aluminum with epoxy powder paint finish.

**IP RATING:** IP65

**DIMENSIONS:** 11 in. (L) x 15 in. (W) x 20.5 in. (H) **WEIGHT:** 45 lbs.



### Century Color 2500L

Now you can really flood your buildings and fill large areas with deep saturated colors. The 2500W lamped Century Color has all the power you will need coupled with smooth distribution of light. Paint your projections with real color.

#### Specifications:

LAMP:  
Type: Philips MSA 2500DE  
Color temperature: 5600°K  
Socket: (P)SfC  
Manufacturers Rated Lamp Life: 2,000 Hours  
Luminous flux: 250,000lm  
COLORS: Cyan, Yellow, Magenta color mixing, white, black out.



SHUTTER: Double blade shutter for linear dimming from 0-100% and blackout

BEAM ANGLE: 60° x 45°  
Tilt Angle: Manually adjustable from 0° to 90°  
Shooting Distance: Approx. 109Yd

CONTROL:  
DMX: 6 Channels  
Stand Alone (auto, 15 programs)  
Master/Slave (auto, 15 programs)

MOTORS: 4 Stepper motors

HOUSING: Metal plate with epoxy powder paint finish

IP RATING: IP44

DIMENSIONS: 770mm LONG x 500mm WIDE x 720mm  
WEIGHT: 154 lbs.



### Century Spot

The Century Spot is a CYM Spot projector which has been created for static architectural purpose; however, it is extremely versatile and can be used also for traditional applications. Thanks to an extremely efficient optic system and its CYM color changer, the light beam can create countless color shades.

#### Specifications:

POWER: 220/230V AC 50/60Hz, 2800w, 220v  
LAMP:  
Type: OSRAM HMI 2500W/SE discharge lamp  
Color temperature: 6000°K  
Socket: G38, single ended  
Manufacturers Rated Lamp Life: 500 Hours  
Luminous flux: 240,000lm  
COLORS: Cyan, Yellow, Magenta color mixing, white, black out.  
SHUTTER: Double blade shutter for linear dimming from 0-100% and blackout  
BEAM ANGLE: 12° ~ 35°  
Tilt Angle: Manually adjustable from 15° to 90°  
Shooting Distance: Approx. 109Yd

CONTROL:  
DMX: 6 Channels  
Stand Alone (auto, 7 programs)  
Master/Slave (auto, 7 programs)

MOTORS: 4 Stepper motors

HOUSING: Metal plate with epoxy powder paint finish

IP RATING: IP44

DIMENSIONS: 770mm LONG x 500mm WIDE x 720mm  
WEIGHT: 165 lbs.