






End Piece Fixtures

These fixtures are designed to work best with SCE-6 solid core or E-S50 stranded cable




Diamond Love

R-150	OFE-60	2M
VBA-2X8.5" (FO-002)		
0.5	0.15	750
1.0	0.3	200
1.5	0.45	100
h (m)	d (M)	E _{max} (lux)

Soleil-2 Swivels

R-150	OFE-60	2M
VBA-2X14" (FO-026)		
1.03	1.0	660
2.06	2.0	165
5.15	5.0	68
h (m)	d (m)	E _{max} (lux)





Saturn Ring

R-150	OFE-60	2M
VBA-2X26" (FO-003)		
0.25	0.27	1300
0.5	0.55	300
1.0	1.1	95
h (m)	d (M)	E _{max} (lux)





Limited stock





Win Flag Swivels

R-150	OFE-60	2M
VBA-2X12.5" (FO-029)		
0.25	0.11	320
0.5	0.22	139
1.0	0.45	17
h (m)	d (M)	E _{max} (lux)



L-Lense

R-150	OFE-60	2M
VBA-2X14" (FO-021)		
1.0	0.5	150
2.0	1.0	47
5.0	2.5	8
h (m)	d (M)	E _{max} (lux)


Big Rocket E-S75 Capable

LS-M150	OFE-60	2M
VBA-2X54" (FO-016)		
0.25	0.7	800
0.5	1.4	200
1.0	2.8	100
h (m)	d (M)	E _{max} (lux)

Bug Eye Swivels E-S75 Capable

R-150	OFE-60	2M
VBA-2X14" (FO-005)		
1.0	0.5	150
2.0	1.0	47
5.0	2.5	8
h (m)	d (M)	E _{max} (lux)




Limited stock





Spear Head E-S75 Capable

R-150	OFE-60	2M
VBA-2X42" (FO-013)		
0.25	0.45	450
0.5	0.9	65
1.0	1.9	16
h (m)	d (M)	E _{max} (lux)


Neptune Ring (Polished brass only) E-S75 Capable

R-150	OFE-60	2M
VBA-2X50" (FO-008)		
0.25	0.6	170
0.5	1.2	60
1.0	2.4	18
h (m)	d (M)	E _{max} (lux)





Crystal Palace

LS-M150	OFE-60	2M
VBA-2X14" (FO-017)		
0.5	0.25	200
1.0	0.5	50
2.0	1.0	17
h (m)	d (M)	E _{max} (lux)





Limited stock





Iceberg E-S75 Capable

R-150	OFE-60	2M
VBA-2X8.5" (FO-014)		
0.5	0.15	750
1.0	0.3	200
1.5	0.45	100
h (m)	d (M)	E _{max} (lux)


Sunny Side-up (Polished brass)

LS-M150	OFE-60	2M
VBA-2X14" (FO-018)		
1.0	0.5	150
2.0	1.0	47
5.0	2.5	8
h (m)	d (M)	E _{max} (lux)


Silver Valley E-S75 Capable

R-150	OFE-60	2M
VBA-2X4.0" (FO-010)		
1.0	0.13	400
2.0	0.27	196
5.0	0.68	37
h (m)	d (M)	E _{max} (lux)





Rare Moon

R-150	OFE-60	2M
VBA-2X42" (FO-030)		
0.25	0.45	200
0.5	0.9	40
1.0	1.8	14
h (m)	d (M)	E _{max} (lux)

Bull Eye E-S75 Capable

R-150	OFE-60	2M
VBA-2X7.4" (FO-011)		
1.0	0.25	1300
2.0	0.5	300
5.0	1.3	79
h (m)	d (M)	E _{max} (lux)






Ceiling Light Fixtures


Unless noted otherwise, our ceiling fixtures normally handle SCE-6 or E-S50 cable. However, some can handle larger cable.




DLCL-4
This fixture swivels




DLCL-5
This fixture swivels




DLCL-6
This fixture swivels




DLCL-7
This fixture swivels



DLCL-8
This fixture will handle up to 150 strands of cable. Comes w/compression fitting



DLCL-12
Glass globe with mirror base



DLCL-16



NEW! Our [LED MR16](#) replacement lamps can be retro-fitted into the ceiling lights! Please call for details.



Landscape Fixtures Paver Lights




GL100



GL105



GL110



FL405
Feature Light
75 Strand Capacity



Lightstick -Path lights for
concrete applications




SL200 Flood
Landscape Fixture
Flexible accent light
with glass lens.
75 strand capacity



SL205 Spotlight
Flexible spotlight with
glass lens.
225 strand capacity

Paver Lights

Paver lights add an elegant touch to any landscape lighting plan. They can be used in pave design, concrete walkways, decks or to illuminate walls. These pavers can be added to an existing fiber optic lighting system with available capacity. Pavers accept 25 strand fiber optic cable each. The paver is constructed of a poly carbonate top and ABS base.



Please call for availability. Pricing is subject to change without notice.