



Projectors-LED Par Cans-Club Wall Washers-UV Lighting

Oil Color

These highly versatile units are designed for choreographic, decorative and promotional projections. Each unit creates an unusual exclusive effect which constantly moves and changes shape and color continually.



Hypnotic Light

As well as the extraordinary color effect created by the fiber optics and moving color Hypnotic projectors, it's also possible to project a pro format (6x6cm.) slide, easily fit special frame supplied with the fixture. The rotation speed of the beam and the slide in both directions.



Technical features:

- Special multi-coloured glass wheel
- Adjustable focus system.
- High quality micromotors
- 6x6 slide frame fitted
- Power cable with CEI 20/22 type
- Safety mains external fuse
- Manufactured in compliance with

Club Wall Washers



Design 150

LAMP OPTIONS:
HSD 150/70 (Osram)
Color temperature: 7000°K
Socket: G12
Manufacturers Rated Lamp Life: 2000 Hours

CDM-SA/T 150/942 (Philips)
Color temperature: 4200°K
Socket: G12
Manufacturers Rated Lamp Life: 6000 Hours

COLORS: Cyan, Yellow, Magenta color mixing, with crossfade effect at various speeds.


SHUTTER/STROBE: Double blade shutter for blackout and linear dimming.
BEAM ANGLE: 21°

HEAD ADJUSTMENT: Tilt 90° (manually adjustable).

CONTROL:
DMX: 6 Channels
Automatic mode with Master/Slave operation.
Lamp and unit time indication.

MOTORS: 8 Stepper motors
HOUSING: Cast Aluminum with epoxy powder paint finish.
IP RATING: IP65

DIMENSIONS: 11 in. (L) x 15 in. (W) x 20.5 in. (H)
WEIGHT: 38.8 lbs.



Design 250

The Design 250 is a projector of innovative, compact, silent color extraordinary performances in terms of color mixing, reliability product complies to CE norms and standards and uses international The Design 250 is particularly suitable for television studios and limelight's, backdrops, inside or outside shops and shopping center almost all architectural applications. The Design 250 features 6 k CYM colour mixing and 2 blades for shutter/dimmer. The product track system, which can adjust the status of product automatically be setup easily via the touch-switches and LCD display. Comes with

Specifications:

POWER: 117V/60Hz
LAMP OPTIONS: Philips CDM-T SA/T150/942 discharge lamp
Color temperature: 4200°K
Socket: G12
Manufacturers Rated Lamp Life: 6000 Hours FLUX: 12,900lm
COLORS: Cyan, Yellow, Magenta color mixing, with crossfade effect speeds.
SHUTTER/STROBE: Double blade shutter for blackout and linear dimming from 0-100%
BEAM ANGLE: 21°
HEAD ADJUSTMENT: Tilt 90° (manually adjustable).
CONTROL:
DMX: 7 Channels
Automatic mode with Master/Slave operation.
Lamp and unit time indication.
2 user memories and 3 preset memories
OTHER FUNCTIONS:
Light level sensor
Timer mode
Remote reset
Lamp Control
MOTORS: 8 Stepper motors
HOUSING: Cast Aluminum with epoxy powder paint finish.
IP RATING: IP65
DIMENSIONS: 11 in. (L) x 15 in. (W) x 20.5 in. (H) **WEIGHT:** 45 lbs.

Multi-Pars

Multi Par CDM



CDM 150
MULTI PAR PROFESSIONAL FLOOD/SPOT LUMINAIRE
Includes 4 lenses:
Very narrow spot - at 40° - 15° beam angle
Narrow spot - at 40° - 19° beam angle
Medium flood - at 40° - 20° x 36° beam angle
Wide Flood - at 35° - 30° x 52° beam angle
Color Temperature: 4200°
Lamp: CDM 150 (not included)
Lamp Life: 6,000 Hrs
Non-dimmable
Power: 117V/60Hz
Available colors: Black, Silver or White

Profile CDM Par Lens



MULTI PAR PROFESSIONAL FLOOD/SPOT LUMINAIRE
Available lenses: 19°, 26° or 36°
Color Temperature: 4200°
Lamp: CD-T 150W (not included)
Lamp Life: 6,000 Hrs
Non-dimmable
Power: 117V/60Hz
Available colors: Black or Off-white
Quantity per carton: 2
Options
Rotating Gobo Holder
Optional Iris

Mini Par CDM



CDM 375
MULTI PAR LUMINAIRE
Color Temperature: 4200°
Lamp: CDM -R70W (not included)
Lamp Life: 6,000 Hrs
Non-dimmable
Power: 117V/60Hz
Available colors: Black or White

UV Lighting

UV 400W Floodlight



Code:
US: 117V 60Hz - W864

Description:
UV fixture suited to large rooms, illuminates a vast area evenly.

Construction:
Metal body, epoxy powder finish
Mounted with adjustable steel bracket
Easy lamp access

Technical specifications:

Lampholder: E/40 ceramic.
100cm power cable to CEI 20/22 norms;
Safety mains external fuse
Safety mesh for lamp protection;
Built-in power factor correction system
Manufactured in compliance with CE norms

Lamp:400W UV

Dimensions and Weight:
26 x 15 x 10 in.
27 lbs.

Black Lantern



Code:
US: 117V 60Hz - W862

Description:
Black Lantern is a compact projector complete with an adjustable support bracket.
It is a powerful UV simulator spot.

Technical specifications:

Dichroic UV light conversion filter
Can be operated in any position
Forced air ventilation
Fuse: 3.15A Easy lamp replacement

Lamp: HQI 150W 6000 hrs life

Dimensions and Weight:
9 x 6.25 x 7.75 in.
21 lbs.

UV 400W Black Gun



Code:
US: 117V 60Hz - W864

Description:
UV fixture suited to large rooms.

Construction:
Metal body, epoxy powder finish
Mounted with adjustable steel bracket
Easy lamp access

Technical specifications:

Lampholder: E/40 ceramic.
100cm power cable to CEI 20/22 norms;
Safety mains external fuse
Safety mesh for lamp protection;
Built-in power factor correction system
Manufactured in compliance with CE norms

Lamp:400W UV