


# iAqua™ SD006 LED pool light



## Features

- Adopts 6pcs 3-in-1 RGB LEDs therefore the mix color effects are much better than monochrome layout.
- Die-casting steel housing and 4mm tempered glass cover. Anti-creep and corrosion preventive. Ip68
- Low voltage running for safety operation.
- Adjustable emitting directions.
- Compatible with normal and DMX512 controllers. Gray scale rates 256.
- Easy connection and installation system.
- Projection distance 50m +
- Long lifespan up to 50000 hours.
- Weight 2.6KG (including the packing box).



## Applications

- Aquatic light
- Pool light
- Waterfall, spring lights
- Projection light
- Entertainment light



## Electrial & Optical characteristics

Model Number	Color	LED Type	Lumen (lm)	Beam angle (degree)	IP	Voltage (V)	Power Consumption (W)
SD-006-D3-R	Red	Edison 1W LED	178.82	8°	68(1m)	24V DC	6
SD-006-D3-Y	Yellow		180.10	8°	68(1m)	24V DC	6
SD-006-D3-G	Green		402.25	8°	68(1m)	24V DC	6
SD-006-D3-B	Blue		60.3	8°	68(1m)	24V DC	6
SD-006-D3-W	White		426.65	8°	68(1m)	24V DC	6
SD-006-D3-WW	Warm White		360.15	8°	68(1m)	24V DC	6
SD-006-D3-NW	Natural White		405.3	8°	68(1m)	24V DC	6
SD-006-RGB	RGB		Edison 3W LED	414.33	8°	68(1m)	24V DC

# wiring diagram



Junction box comes with 5 to 10 holes so 4 to 9 iAqua can be installed in this way.

